




MECHANICAL INFORMATION


AUX COMM - RS232 Communication Connector			
Connector Information 3-pin, 2.5 mm spaced, enclosed, friction lock header			
Details Phoenix: Plug P/N 1881338			
Mating Connector	Included with Drive	Yes	
3 ISO GND 2 RS232 TX 1 RS232 RX			


























MOUNTING DIMENSIONS





PART NUMBERING INFORMATION



DigiFlex® Performance™ series of products are available in many configurations. Note that not all possible part number combinations are offered as standard drives. All models listed in the selection tables of the website are readily available, standard product offerings.

ADVANCED Motion Controls also has the capability to promptly develop and deliver specified products for OEMs with volume requests. Our Applications and Engineering Departments will work closely with your design team through all stages of development in order to provide the best servo drive solution for your system. Equipped with on-site manufacturing for quick-turn customs capabilities, ADVANCED Motion Controls utilizes our years of engineering and manufacturing expertise to decrease your costs and time-to-market while increasing system quality and reliability. Feel free to contact Applications Engineering for further information and details.

Examples of Customized Products

- Optimized Footprint
- ▲ Private Label Software
- ▲ OEM Specified Connectors
- ✓ No Outer Case
- ✓ Increased Current Resolution
- ✓ Increased Temperature Range
- Custom Control Interface
- ▲ Integrated System I/O

- ▲ Tailored Project File
- ▲ Silkscreen Branding
- Optimized Base Plate
- ▲ Increased Current Limits
- ▲ Increased Voltage Range
- Conformal Coating
- ▲ Multi-Axis Configurations
- ▲ Reduced Profile Size and Weight

All specifications in this document are subject to change without written notice. Actual product may differ from pictures provided in this document.