

STM23C-3CN

NEMA 23 Integrated CANopen Drive+Motor



Product Features

- *Sophisticated current control*
- *Anti-resonance*
- *Torque ripple smoothing*
- *Microstep emulation*
- *NEMA 23 frame size*
- *DS301 and DSP402 supported*
- *Profile position and velocity modes*
- *Several homing modes*
- *Objects for Q programming*
- *Objects for data registers*
- *RS-232 port for programming*



Description

The STM23C-3CN integrated stepper is a drive+motor unit, fusing a NEMA 23 step motor and a sophisticated 5.0 A/phase (peak-of-sine) stepper drive into a single device. Power to the drive, located at the rear of the motor, must be supplied by an external DC supply. See Related and Recommended Products below for compatible 24 and 48 volt DC [power supplies](#).

The STM23C-3CN integrated stepper is designed to operate on a CANopen communication network and conforms to Can in Automation (CiA) DS301 and DSP402 specifications. It supports Profile Position, Profile Velocity, and Homing modes, as well as the ability to run stored Q programs via Applied Motion-specific CANopen objects. All STM23 units are setup and configured using Applied Motion's [ST Configurator™](#) software.

Each STM23 integrated stepper comes with 3 digital inputs, 1 digital output, and 1 analog input. The digital inputs accept signals of 5-24 VDC and can be used for connecting pulse & direction signals, end-of-travel limit switches, jog switches, quadrature encoder signals, PLC outputs, sensors, or many other signal types. The digital output can be connected to PLC inputs, counters, lights, relays, or other devices. The analog input accepts 0-5 VDC signals and can be used for velocity and position control.

The STM23C-3CN comes with an RS-232 port for programming and a CANopen port for network communications.

Specifications

Part Number	STM23C-3CN
Supply Voltage	12-70 VDC
Supply Voltage Type	DC
Control Modes	• CANopen

Communication Ports	<ul style="list-style-type: none"> • RS-232 • CANopen
Encoder Feedback	No
Step Resolution	<ul style="list-style-type: none"> • Full • Half • Microstepping • Microstep Emulation
Idle Current Reduction	0-90%
Setup Method	Software setup
Digital Inputs	3
Digital Outputs	1
Analog Inputs	NA
Circuit Protection	<ul style="list-style-type: none"> • Short circuit • Over-voltage • Under-voltage • Over-temp
Status LEDs	1 red, 1 green
Frame Size	NEMA 23
Holding Torque	210 oz-in
Step Angle	1.8 deg
Rotor Inertia	6.51E-03 oz-in-sec ²
Length	4.50 inches
Weight	42 oz
Operating Temperature Range	0 to 85 °C
Ambient Temperature Range	0 to 40 °C
Ambient Humidity	90% max, non-condensing
Insulation Class	Class B (130 °C)
Maximum Radial Load	NA
Maximum Thrust Load	NA
Shaft Run Out	NA
Radial Play	NA
End Play	NA
Perpendicularity	NA
Concentricity	NA