

Extruded Stage Catalog Numbers

Motor		LMBL18A		
Cont Force		80 Lbs [356N]		
Peak Force		240 Lbs [1068N]		
Stroke		Overall Length		Stage
inch	meter	inch	meter	Catalog Number
0.20	0.01	21.05	0.53	LSX1TEBL14AF2
2.00	0.05	22.85	0.58	LSX1TEBL14A2
5.60	0.14	26.45	0.67	LSX1TEBL14A5
11.00	0.28	31.85	0.81	LSX1TEBL14A11
14.60	0.37	35.45	0.90	LSX1TEBL14A14
20.00	0.51	40.85	1.04	LSX1TEBL14A20
25.40	0.65	46.25	1.17	LSX1TEBL14A25
30.80	0.78	51.65	1.31	LSX1TEBL14A30
34.40	0.87	55.25	1.40	LSX1TEBL14A35
39.80	1.01	60.65	1.54	LSX1TEBL14A40
45.20	1.15	66.05	1.68	LSX1TEBL14A45
50.31	1.28	71.45	1.81	LSX1TEBL14A50
55.17	1.40	76.85	1.95	LSX1TEBL14A55
60.03	1.52	82.25	2.09	LSX1TEBL14A60
64.89	1.65	87.65	2.23	LSX1TEBL14A64
69.75	1.77	93.05	2.36	LSX1TEBL14A69
74.61	1.90	98.45	2.50	LSX1TEBL14A74
79.47	2.02	103.85	2.64	LSX1TEBL14A79
85.95	2.18	111.05	2.82	LSX1TEBL14A85
90.81	2.31	116.45	2.96	LSX1TEBL14A90
95.67	2.43	121.85	3.09	LSX1TEBL14A95
100.53	2.55	127.25	3.23	LSX1TEBL14A100
105.39	2.68	132.65	3.37	LSX1TEBL14A105
110.25	2.80	138.05	3.51	LSX1TEBL14A110
115.11	2.92	143.45	3.64	LSX1TEBL14A115
119.97	3.05	148.85	3.78	LSX1TEBL14A119
124.83	3.17	154.25	3.92	LSX1TEBL14A124
129.69	3.29	159.65	4.06	LSX1TEBL14A129
134.55	3.42	165.05	4.19	LSX1TEBL14A134
139.41	3.54	170.45	4.33	LSX1TEBL14A139
145.89	3.71	177.65	4.51	LSX1TEBL14A145
149.13	3.79	181.25	4.60	LSX1TEBL14A150

PRODUCT
OVERVIEW

MOTION
CONTROLLERS

LINEAR
BRUSHLESS

DC BRUSHED
LINEAR

LINEAR
STEPPERS

LINEAR
INDUCTION

NON-COMMUTATED
DC LINEAR

POSITIONING
STAGES