



|                                       |
|---------------------------------------|
| TOL UNLESS SPEC.                      |
| 2 PLC DECIMALS = $\pm$ .020           |
| 3 PLC DECIMALS = $\pm$ .005           |
| ANG= $\pm$ .5° RADII= $\pm$ .020±.005 |

|                    |                 |                   |  |                 |  |                       |  |                            |  |                     |  |
|--------------------|-----------------|-------------------|--|-----------------|--|-----------------------|--|----------------------------|--|---------------------|--|
| CUST. NAME: BALDOR |                 | CUST. P.O.: -     |  | CERTIFIED BY: - |  | TORQUE: 19.7 IN. LBS. |  | INSUL: B                   |  | FLA: 1              |  |
| H.P.: 1/12         |                 | MTG: -            |  | TYPE: DCPM      |  | R.P.M.: 250           |  | VOLTS: 90 DC               |  | ENCL: TENV PHASE: - |  |
| FREQ: -            |                 | FRAME: 125-PSSH-0 |  | REMARKS:        |  |                       |  |                            |  |                     |  |
| REV: A             | LOADED TO ACAD. |                   |  |                 |  |                       |  |                            |  |                     |  |
| VΣ060Σ             |                 | SCALE: .5=1       |  | BY: JD          |  | REVISED: 06/20/96     |  | <b>BALDOR ELECTRIC Co.</b> |  |                     |  |
| FILE: CKA00004674  |                 | TDR: 0099433      |  | LAYOUT DRAWING  |  |                       |  |                            |  |                     |  |