

MILITARY SPECIFICATION SHEET

SYNCHRO, CONTROL TRANSMITTER, TYPE 23CX4D

This amendment forms a part of Military Specification Sheet MIL-S-20708/45D dated 19 December 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Table II and notes above and below Table II - Delete entirely and substitute the following:

"TABLE II. Military Part Number Variant Characteristics

MILITARY PART NO. <u>1/</u>	SHAFT DIAMETER NOMINAL	SHAFT STYLE	TERMINATION	L' DIMENSION TO STOP ON SHAFT	L DIMENSION FREE SHAFT LENGTH
M20708/45-01D	.2405	Splined	Terminal Board	.676 ± .010	.719 ± .010

1/ Military part number M20708/45-01D shall be the NATO Standard.

1/ The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation."

FSC 5990

MIL-S-20708/45D
AMENDMENT 1

Add a new Table III and note as follows:

"TABLE III. Military Part Number Cross-References.

SUPERSEDED MILITARY PART NUMBERS		NEW MILITARY PART NUMBERS
MIL-S-20708/45D	MIL-S-20708/45C	
M20708/45D-001	M20708/45-001	M20708/45-01D

NOTE: All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation/ modification. Part number changes do not affect form, fit, or function of the synchros listed therein."

Custodians:

Army -- AR
Navy -- AS
Air Force -- 85

Preparing activity:

Navy -- AS
Project No. 5990-0313-28

Review activities:

Army -- ME
Navy -- OS, SH, EC
Air Force -- 11, 17, 19, 99
DSA -- ES

User activities:

Army --
Navy -- MC, CG
Air Force --

MIL-S-20708/45E
30 July 1987

SUPERSEDING
MIL-S-20708/45D
19 December 1968

MILITARY SPECIFICATION SHEET
SYNCHRO, CONTROL TRANSMITTER, TYPE 23CX4D

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of MIL-S-20708.

TABLE I: Requirements.

Requirement	Value	Unit	Tolerance
Frequency	400	Hz	±1%
Primary Voltage	115	volts	±1%
Primary Current	245	milliamps	maximum
Primary Power	2.1	watts	maximum
Impedance:			
Z _{ro}	470-580	ohms	min.-max.
Z _{ss}	21.6-26.0	ohms	min.-max.
Impedance Angle:			
Z _{ro}	84.0-87.5	degrees	min.-max.
Z _{ss}	42.0-47.0	degrees	min.-max.
Transformation Ratio	0.783	-----	±2%
Phase Shift (Lead)	1.0	degrees	±1.0
Electrical Error	6.0	minutes	maximum
Null Voltage:			
Total	48	millivolts	maximum
Fundamental	32	millivolts	maximum
Friction Torque	0.2	ounce-inches	maximum
Radial Play	0.0010	inches	maximum
End Play	0.0025	inches	±0.0020
Temperature Rise	20	degrees (C)	maximum

MIL-S-20708/45E

TABLE II. Military part number variant characteristics.

Military Part No. 1/	A ±.010	B ±.010	G Maximum	Shaft Style	Terminal End	U +.0000
M20708/45-01D	.676	.719	3.160	Splined	Terminal Board	.2405

1/Military part number M20708/45-01D shall be the NATO standard.

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

TABLE III. Military part number cross-references.

SUPERSEDED MILITARY PART NUMBERS		NEW MILITARY PART NUMBERS
MIL-S-20708/45D	MIL-S-20708/45C	M20708/45-01D
M20708/45D-001	M20708/45-001	

NOTE: All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation modification. Part number changes do not affect form, fit, or function of the synchros listed therein.

Custodians:

Army-AR
Navy-AS
Air Force-85

Review Activities:

Army-MI,AV
Navy-OS
Air Force-11,17,99
DLA-ES

User Activities:

Navy-MC,CG

Preparing Activity:

Navy-AS

(Project 5990-0334-42)

TABLE I

Requirement	Value	Unit	Tolerance
Frequency	400	Hz	+1%
Primary Voltage	115	volts	+1%
Primary Current	245	milliamps	maximum
Primary Power	1.7	watts	nominal
Impedance:			
Zro	470-580	ohms	min.-max.
Zss	21.6-26.0	ohms	min.-max.
Impedance Angle:			
Zro	84.0-87.5	degrees	min.-max.
Zss	42.0-47.0	degrees	min.-max.
Transformation Ratio	0.783	-----	+2%
Phase Shift	1.0(lead)	degrees	±1.0
Electrical Error	6.0	minutes	maximum
Null Voltage:			
Total	48	millivolts	maximum
Fundamental	32	millivolts	maximum
Friction Torque	0.2	ounce-inches	maximum
Radial Play	0.0010	inches	maximum
End Play	0.0025	inches	+0.0020
Temperature Rise	20	degrees(C)	maximum

Part number: M20708/45D plus applicable dash number from Table II.

TABLE II

DASH NO.	SHAFT DIAMETER	SHAFT STYLE	TERMINAL END	L' DIMENSION TO STOP ON SHAFT	L' REFERENCE FREE SHAFT LENGTH
*-001	.2405	Splined	Terminal Board	.676 ± .010	.719 ± .010

*Dash number -001 shall be the NATO standard.

Custodians: Army-MU Navy-AS Air Force-85	Review Activities: Army-EL,MI,MO,AV,MU Navy-SH,OS,AS Air Force-11,17.85 DSA-ES	User Activities: Navy-SH,OS,AS,MC,CG	Preparing Activity: Navy-AS Project No. 5990-0187
--	---	--	--

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION
MIL-S-20708/45D

ORGANIZATION (of submitter)

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT

\$

MATERIAL PROCURED UNDER A.

DIRECT GOVERNMENT CONTRACT

SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

 YES

 NO

IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)

DATE

DD FORM 1426
1 APR 62

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

E-9879

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Weapons Engineering Standardization Office (Code X)
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

FOLD