

MILITARY SPECIFICATION SHEET

SYNCHRO, CONTROL TRANSMITTER, TYPE 23CX6D

This amendment forms a part of Military Specification Sheet MIL-S-20708/52C dated 19 December 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Table II and notes above and below Table II - Delete entirely and substitute the following:

"TABLE II. Military Part Number Variant Characteristics

MILITARY PART NO. <u>1/</u>	SHAFT DIAMETER NOMINAL	SHAFT STYLE	TERMINATION	L' DIMENSION TO STOP ON SHAFT	L DIMENSION FREE SHAFT LENGTH
M20708/52-01D	.2405	Splined	Terminal Board	.676 \pm .010	.719 \pm .010

1/ Military part number M20708/52-01D shall be the NATO Standard.

1/ The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation."

FSC 5990

MIL-S-20708/52C
AMENDMENT 1

Add a new Table III and note as follows:

"TABLE III. Military Part Number Cross-References

SUPERSEDED MILITARY PART NUMBERS		NEW MILITARY PART NUMBERS
MIL-S-20708/52C	MIL-S-20708/52B	
M20708/52C-001	M20708/52-001	M20708/52-01D

NOT: All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation modification. Part number changes do not affect form, fit, or function of the synchros listed therein."

Custodians:

Army - AR
Navy - AS
Air Force - 85

Preparing activity:

Navy - AS
Project No. 5990-0313-33

Review activities:

Army - ME
Navy - OS, SH, EC
Air Force - 11, 17, 19, 99
DSA - ES

User activities:

Army -
Navy - MC, CG
Air Force -

MIL-S-20708/52D
30 July 1987

SUPERSEDING
MIL-S-20708/52C
19 December 1968

MILITARY SPECIFICATION SHEET
SYNCHRO, CONTROL TRANSMITTER, TYPE 23CX6D

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of MIL-S-20708.

TABLE I. Requirements.

Requirement	Value	Unit	Tolerance
Frequency	60	Hz	±1%
Primary Voltage	115	volts	±1%
Primary Current	80	milliamps	maximum
Primary Power	1.7	watts	maximum
Impedance:			
Z _{ro}	1450-1700	ohms	min.-max.
Z _{ss}	155-310	ohms	min.-max.
Impedance Angle:			
Z _{ro}	79.0-83.0	degrees	min.-max.
Z _{ss}	10.0-15.0	degrees	min.-max.
Transformation Ratio	0.783	-----	±2%
Phase Shift (Lead)	6.5	degrees	±1.5
Electrical Error	6.0	minutes	maximum
Null Voltage:			
Total	60	millivolts	maximum
Fundamental	30	millivolts	maximum
Friction Torque	0.20	ounce-inches	maximum
Radial Play	0.0010	inches	maximum
End Play	0.0025	inches	±0.0020
Temperature Rise	20	degrees (C)	maximum

MIL-S-20708/52D

TABLE II. Military part number variant characteristics.

Military Part No. 1/	A ±.010	B ±.010	G Maximum	Shaft Style	Terminal End	U +.0000
M20708/52-01D	.676	.719	3.160	Splined	Terminal Board	.2405

1/Military part number M20708/52-01D shall be the NATO standard.

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

TABLE III. Military part number cross-references.

SUPERSEDED MILITARY PART NUMBERS		NEW MILITARY PART NUMBERS
MIL-S-20708/52C	MIL-S-20708/52B	
M20708/52C-001	M20708/52-001	M20708/52-01D

NOTE: All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation modification. Part number changes do not affect form, fit, or function of the synchros listed therein.

Custodians:

Army-AR
Navy-AS
Air Force-85

Preparing Activity:

Navy-AS

(Project 5990-0334-48)

Review Activities:

Army-MI,AV
Navy-OS
Air Force-11,17,99
DLA-ES

User Activities:

Navy-MC,CG

TABLE I

Requirement	Value	Unit	Tolerance
Frequency	60	Hz	+1%
Primary Voltage	115	volts	+1%
Primary Current	80	milliamps	maximum
Primary Power	1.4	watts	nominal
Impedance:			
Z _{ro}	1450-1700	ohms	min.-max.
Z _{ss}	155-310	ohms	min.-max.
Impedance Angle:			
Z _{ro}	79.0-83.0	degrees	min.-max.
Z _{ss}	10.0-15.0	degrees	min.-max.
Transformation Ratio	0.783	-----	+2%
Phase Shift	6.5	degrees	±1.5
Electrical Error	6.0	minutes	maximum
Null Voltage:			
Total	60.0	millivolts	maximum
Fundamental	30.0	millivolts	maximum
Friction Torque	0.20	ounce-inches	maximum
Radial Play	0.0010	inches	maximum
End Play	0.0025	inches	+0.0020
Temperature Rise	20.0	degrees(C)	maximum

Part number: M20708/52C plus applicable dash number from Table II.

TABLE II

DASH NO.	SHAFT DIAMETER	SHAFT STYLE	TERMINAL END	L' DIMENSION TO STOP ON SHAFT	L REFERENCE FREE SHAFT LENGTH
*-001	.2405	Splined	Terminal Board	.676 ± .010	.719 ± .010

*Dash number -001 shall be the NATO standard.

Custodians:	Review Activities:	User Activities:	Preparing Activity:
Army-MU	Army-EL,MI,MO,AV,MU	Navy-SH,OS,AS,MC,CG	Navy-AS
Navy-AS	Navy-SH,OS,AS		
Air Force-85	Air Force-11,17.85		Project No. 5990-0078
	DSA-ES		

SPECIFICATION ANALYSIS SHEET		Form Approved Budget Bureau No. 115-5594
<u>INSTRUCTIONS</u>		
This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).		
SPECIFICATION MIL-S-20708/52C		
ORGANIZATION (of submitter)		CITY AND STATE
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT \$
MATERIAL PROCURED UNDER A <input type="checkbox"/> DIRECT GOVERNMENT CONTRACT <input type="checkbox"/> SUBCONTRACT		
1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? A. GIVE PARAGRAPH NUMBER AND WORDING.		
B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.		
2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID.		
3. IS THE SPECIFICATION RESTRICTIVE? <input type="checkbox"/> YES <input type="checkbox"/> NO IF "YES", IN WHAT WAY?		
4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)		
SUBMITTED BY (Printed or typed name and activity)		DATE

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Weapons Engineering Standardization Office (Code X)
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

FOLD

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-515/A-3698